### DIGITAL DIALYSATE METERS



The D-6 Dialysate Meter has received FDA 510(k) acceptance for use as a medical device for testing dialysate. FDA Device Manufacturing License #s: 65387 (CA), 2020976 (Federal)

**Water Quality Instrumentation** Accuracy • Reliability • Simplicity

. . Since 1957

### DIGITAL DIALYSATE METERS™

#### Advanced Design • Superior Performance

Standardized to 3 solution types for extremely accurate temperature compensation and TDS conversion in a wide variety of applications (Default is NaCI)

No in-line components, eliminating the risk of cross-contamination with patient dialysate stream

Internal sensors offer increased durability and are included with instrument

Ability to test 7 solution parameters: Conductivity, pH, TDS, Resistivity, **ORP, Free Chlorine and Temperature** 

Four-digit display for full 9999 readings, with autoranging capability up to 200 mS/200 ppt

Powerful microprocessor based surface mount circuitry

Memory for up to 100 date-timestamped readings

Display prompts for simple pH calibration

**Real Time Clock** 





**Both DIGITAL** DIALYSATE METERS are capable of wireless data transfer with bluDock™ option installed\*

\*Digital Dialysate Meter measurement data transferred to a personal computer using the wireless communication option is for record-keeping purposes only and is not intended for use in making treatment or diagnostic decisions.

## ACCURATE

dialysate quality checks and equipment calibration

### RELIABLE

internal sensors, stable circuitry, nonvolatile memory

## SIMPLE TO USE

one-touch measurement functions

## TRUSTE

ince 1957, the Myron L Company has designed and manufactured highly reliable analytical instruments for a wide variety of demanding applications. Thousands of professionals around the world rely on the performance of our instruments every day. Myron L is also the manufacturer of the original Dialysate Meter™, trusted by Hemodialysis professionals for over 40 years. And we offer a full line of portable handheld testing instruments and monitor/controllers for every aspect of water quality analysis and control. The new DIGITAL DIALYSATE METER is designed to simplify testing across a variety of applications in your clinic: Dialysate Testing, Water Quality Control, System Disinfection, Equipment Calibration and Effluent Monitoring. This instrument does the work of up to 7 different instruments. with fast accurate results and user-intuitive interface.

### **Definitive Dialysate Testing**

The D-6 and D-4 DIGITAL DIALYSATE METERS are specifically designed to test both acetate and bicarbonate dialysate quality. There are no strips or reagents that expire or subjective interpretation of results. Measurements display immediately.

## Quality Assurance in Water Treatment for Hemodialysis

DIGITAL DIALYSATE METERS are a cost effective solution for your clinic's water treatment testing. Manage Reverse Osmosis Systems, DI Banks, Chlorine Removal, Ultrafiltration and other processes required for dialysate grade water. Test Conductivity, Resistivity, TDS, pH, ORP and Temperature of feed and product water in unit processes. Use measurements as independent checks against automatic systems of control and for monitor/controller calibration.

### **Disinfection System Maintenance**

MYRON L'S DIGITAL DIALYSATE METERS deliver results when you need them where you need them. Monitor levels of residual (oxidizing/reducing) sanitizer during system maintenance. Use ORP and Free Chlorine parameters to ensure proper concentrations in disinfection loops and for jug disinfection. Ensure removal of disinfectant from hemodialysis systems and storage tanks after rinsing.

#### Hemodialysis Equipment Calibration

DIGITAL DIALYSATE METERS are a fast easy way to calibrate hemodialysis machines. Both instruments deliver accuracy of ±0.01 pH unit and ±0.1% of reading at calibration point for Conductivity, Resistivity and TDS readings.

### **Compliance in Effluent Monitoring**

DIGITAL DIALYSATE METERS measure water quality parameters that affect the health and safety of the environment. Monitor parameters required by your discharge permit for compliance with federal, state and local regulations quickly and easily.

#### **Easy Setup**

Instruments do NOT need sterilization. Internal sensors require the user to place the sample in the instrument, preventing cross contamination of patient dialysate stream.

#### **Easy to Use**

The DIGITAL DIALYSATE METER is a prime example of how high-tech engineering can greatly simplify and streamline a task. Whether in the lab, or testing water and dialysate quality on the spot, merely:

- 1. Fill the cell cup
- 2. Push a parameter key
- 3. Take the reading

Temperature compensation and range selection are both rapid and automatic. You immediately get a standard, numerical digital readout — eliminating all subjectivity. Up to 100 date-time-stamped readings can be stored in non-volatile memory. The DIGITAL DIALYSATE METER is lightweight, portable, buoyant and waterproof.

#### **Easy to Maintain**

You never have to return a DIGITAL DIALYSATE METER to the manufacturer for calibration. All calibrations are quickly accomplished by pressing the ▲ or ▼ keys to agree with our NIST traceable Standard Solution. When pH calibration is necessary, display prompts guide the user and make sure the correct buffer is being used. Plus, all parameters (excluding factory-set temperature) have an internal electronic setting that can be used for field calibration and as a check on pH/ORP sensor life.

#### **Advanced Features**

- Fully automatic temperature compensation.
- Auto-shutoff maximizes the life of the single 9V battery to more than 100 hours/5000 tests.
- Non-volatile microprocessor provides data back-up, even when the battery is changed. This assures all calibrations and memory data will be retained.
- •Extended life pH/ORP sensor is user replaceable in the field.

#### **Reportable Records**

DIGITAL DIALYSATE METERS make it easy to record, analyze, archive, and report water quality data with the optional bluDock™ accessory package. Simply enter data transfer mode and download stored data to any computer through the bluDock software interface. The data can then be imported into any program necessary for record-keeping and analysis. The bluDock is a fast and easy way to comply with record-keeping and reporting requirements.

#### **More from Myron L**

High quality analog handheld D-1 and D-2 Dialysate Meters™ are available for testing dialysate conductivity in both acetate and bicarbonate solutions.



# Myron L Benefits that <u>SAVE</u> You <u>TIME</u> & <u>MONEY</u>

**Low Maintenance** 

**EASY** User Friendly Interface

Replaces up to 7 different instruments

Learn, Use and Train <u>FAST</u> on only one instrument for all water quality testing

FREE live technical support with little to no wait time

RELIABLE manufacturer of the original Dialysate Meter<sup>TM</sup>, Myron L Company has served hemodialysis professionals for over 40 years

Call +1-760-438-2021 or visit our website for details: www.myronl.com



D-4	D-6
Conductivity, TDS, Resistivity, Temperature	Conductivity, TDS, Resistivity, pH, ORP, Temperature
•	•
•	•
•	•
	•
•	•
•	•
•	•
	Conductivity, TDS, Resistivity,

#### **Specifications**

Display	4 Digit Liquid Crystal Display
Dimensions: LxWxH	196 x 68 x 64 mm/ 7.7 x 2.7 x 2.5 in.
Weight	352 g/12.4 oz.
Case/conductivity cell material	VALOX*
Cell capacities	pH/ORP: 1,2 ml/0.04 oz. Cond/Res/TDS: 5 ml/0.2 oz.
Power	9V alkaline battery
Battery life	>100 hours (5000 readings)
Operating/storage temperature	0 – 55°C/32 – 132°F
Protection ratings  *®SABIC INNOVATIVE PLASTICS	IP67/NEMA 6 Waterproof to 1 meter/3 feet

#### **Parameters**

	Conductivity	TDS	Resistivity	рН	ORP mV/ppm Free Chlorine	Temperature
Ranges						
	0.1(<1000 μS)	0.1(<1000 ppm)	0.1(<1000 ΚΩ)		0.1 ppm	
	1(<10 mS) 0.01(<100 mS)	1(<10 ppt) 0.01(<100 ppt)	0.1(>1 MΩ)			
	0.1(<200 mS)	0.1(<200 ppt)				
					± 2.5% of reading ppm	
Auto Temperature						

YRON L Company

#### **Accessories**

MODEL: BLUDOCK

MODEL: MCD

#### bluDock™ Accessory Package



DIALYSATE METER with data are available (must

RECOMMENDED VALUES: NaCl-14.0, 442-3000 (TDS)

available in 2 oz/59 ml, 1 qt/1 L, and 1 gal/3,8 L.

be specified when placing instrument order).



IGITAL

oz/59 ml, 1 qt/1 L, and 1 gal/3,8 L.

oz/59 ml.

oz/59 ml, 1 qt/1 L, and 1 gal/3,8 L.

MODEL: SS2OZ, SSQ and SSG

MODEL: PKD

MODEL: UCC (Blue)



\*configuration may vary

MODEL: SC-XX if ordered with solution SCATF if ordered separately UCCDT (Desert Tan)

MODEL: UPP

MODEL: RPR



**Built on Trust** 



IGITAL DIALYSATE METERS have a Two (2) Year Limited Warranty. The pH/ORP sensors have a Six (6) Month Limited Warranty. Warranty is limited to the repair or replacement of the Digital Dialysate Meter only, at our discretion. Myron L Company assumes no other responsibility or liability.

> Legacy Pumps & Instruments, LLC PO Box 426 Mineral Wells, TX 76068-0426 214-384-5303 -or- 817-793-0485 www.legacypumpsllc.com

